

## **ROTARY TILLERS**

15 to 55 PTO HP



Turn hard ground into a perfect seed bed quickly and easily using the economical Worksaver rotary tiller. Ideal for gardening, landscaping, orchards, or any soil operation.

Each model is designed rugged and built to last many years. All models feature curved or "L" blades, oil-bathed over-sized chain drive, depth adjustment on skids, and adjustable lower hitch points. A rear deflector keeps soil and debris beneath the tiller for through pulverization. Gearbox is protected by either a shear-bolt or slip clutch PTO driveline.

	T 25 SERIES	T 55 SERIES				
MODEL	T25-42	T25-	50	T40-58	T40-66	T55-74
HP Rating	25 Max.	25 Max.		40 Max.	40 Max.	55 Max.
HP Req. Range	15 – 18 hp	18 – 22 hp		32 – 38 hp	35 – 40 hp	45 – 55 hp
Working Width	42 in.	50 in.		58 in.	66 in.	74 in.
Working Depth	5 in. max.	5 in. max.		6 in. max.	6 in. max.	7 in. max.
PTO Driveline	Shear-bolt	Shear-bolt		Shear-bolt	Shear-bolt	Slip-Clutch
Driveline Options	-	-		Slip-Clutch	Slip-Clutch	-
Drive	Oil Bath	Oil Bath		Oil Bath	Oil Bath	Oil Bath
	Oversized	Oversized		Oversized	Oversized	Oversized
	Chain	Chain		Chain	Chain	Chain
Depth Adjust.	Skid Shoes	Skid Sh	noes	Skid Shoes	Skid Shoes	Skid Shoes
Hitch – 3 pt.	Cat. 0	Cat. 0		Cat. I	Cat. I	Cat. I
Offset	11 ½ Total	11 1/2 Total		7 ½ from	7 ½ from	7 ½ from
	Gearbox and	Gearbox and		center left or	center left or	center left or
	hitch move as	hitch move as		right	right	right
	one unit	one unit				
No. of Blades	20	24		28	32	36
Type	Curved	Curve	ed	"L" Shaped	"L" Shaped	"L" Shaped
Parking Stand	-	-		Optional	Optional	Optional
Shipping Weight	283 lb.	308 l	b.	478 lb.	525 lb.	790 lb.
Stock No.	320200	3202	05	320215	320220	320230



Information Provided by: